



Eco Jet Stationary Extraction Filter Systems

AL-KO PROFI JET® extraction systems are planned and built from a modular construction kit according to your needs. The extremely low sound emissions and the fire and explosion protection certificates make it easier for you to obtain approval. Thanks to its modular design, your stationary AL-KO PROFI JET® system grows with your business, which means additional security of investment for you.

[Read More](#)

SKU:

Price:

Categories: [AL-KO Air Technologies](#), [Air Extraction](#), [Stationary Filter Systems](#)

Product Description

AL-KO ECO JET® systems have been proving themselves in practice, day after day, for years. They are characterised by high reliability and are particularly energy-efficient. The proverbial reliability, the long filter service life and the excellent accessibility to AL-KO ECO JET® systems give you the security to not only lower your costs but also to invest in the future of your business.

Benefits

- Certified to H3 and EW 90
- Low acquisition costs
- Low operating costs
- Complete heat recovery
- Low noise emissions
- Longer filter service life
- Manufactured in Germany

Technical data

	3 A-L-XL	4 A-L-XL	5 A-L-XL	6 A-L-XL
Vacuum	3,700 - 4,200 Pa	2,500 - 4,200 Pa	2,100 - 3,700 Pa	2,250 - 3,000 Pa
Motor rating	5.5 - 11 kW	7.5 - 15 kW	11 - 15 kW	11 - 15 kW
Flow rate	2,500 - 4,200 m³/h	6,045 - 10,000 m³/h	6,045 - 10,000 m³/h	7,770 - 10,000 m³/h
Filter area	23 - 38.8 m²	28.8 - 58.2 m²	40.3 - 77.6 m²	51.8 - 97 m²
Depth x Length	1,225 x 2,440 mm	1,225 x 3,084 mm	1,225 x 3,950 mm	1,225 x 4,563 mm
Height variant A:	3,004 mm	3,004 mm	3,004 mm	3,004 mm
Height variant A-L:	3,609 mm	3,609 mm	3,609 mm	3,609 mm
Height variant A-XL:	4,104 mm	4,104 mm	4,104 mm	4,104 mm